
Installation Instructions





41888 32VDC/9VDC/24VAC HARNESS REPLACEMENT

41888 32VDC/9VDC/24VAC HARNESS REPLACEMENT Installation Instructions

OVERVIEW

PN: 41888 Ø

2 DCI Edge

INTRODUCTION

BEFORE YOU BEGIN

Study the unit overview in this booklet and layout dimensions from the owner's manual. Make sure the planned location will have the necessary space available for installation, including room for travel of the chair's base and backrest.

Open all containers and review the contents. It may be helpful to locate all kits containing accessories. (Smaller parts are often packaged together to avoid being lost.)

Locate all documentation supplied with the package. Manuals and installation sheets may be found in one or more boxes accompanying their respective components. Set aside the owner's manual for the end user to review.

TABLE OF CONTENTS

Overview		2
Introducti	on	3
41888 32	VDC/9VDC/24VAC	
Harness	Replacement Instructions	4

SYMBOLS USED IN THIS MANUAL

The following symbols may be used throughout this product manual:



WARNING: Failure to carefully follow the described procedure may result in damage to the equipment or the operator.



CAUTION: Failure to carefully follow the described procedure may result in damage to the equipment.



NOTE: Take note of additional important information. Not a warning or caution.



ELECTRICAL HAZARD: Risk of electrical shock present. Ensure that power is disconnected before attempting procedure.

REGULATORY INFORMATION

Regulatory information is delivered with DCI Edge dental equipment as mandated by agency requirements and can be found in the accompanying Instructions for Use for this device.

PACKAGE CONTENTS

- PN 41888 Harness
- Installation Instructions

TOOLS NEEDED FOR INSTALLATION

- #1/#2 Phillips Screwdriver (Figure 1, item 1)
- 0.125" Slotted Screwdriver (item 2)
- 7/64" Hex Key (item 3)
- Side Cutting Pliers (item 4, optional)
- DCI Umbilical Tubing Stringer (PN 8094, item 5, optional)






Figure 1. Tools needed for installation


PREPARATION



DCI Edge 5







5 Remove the power harness from the chair and unit.

DCI edge 🛛

CONNECTING THE NEW 41888 HARNESS

- Connect the new 41888 harness to the chair transformer and any auxiliary power using the available terminals (see Figure 9, Item 1).
- **2** Feed the harness through the unit arms and into the unit head (see Figure 10).





Figure 11. Connecting the new harness to the terminal block

Figure 12. 41888 harness connection diagram



www.dcionline.com 800-624-2793

